


Technical Data Sheet

Product Description

Graphite Copper Foil

Thermally Conductive Graphite Copper is a thermal interface material with super high conductivity generated from a carbon/copper film structure. Nano-copper/carbon foil thermally conductive tape uses copper foil as a carrier and is coated with a thermally conductive acrylic adhesive. It provides an excellent heat conduction path between the heating element and the heat sink.



Material Properties

- High thermal conductivity
- Excellent Shielding properties
- Lightweight/ thin
- Good shielding effectiveness
- Excellent heat-transfer path between the heat-generator and heat sink

Applications

- ✓ Automotive electronics
- ✓ Computers and servers
- ✓ Communication equipment
- ✓ Consumer electronics
- ✓ Aerospace and medical devices
- ✓ LED lighting equipment
- ✓ Displays



EVSU004-1/2 Graphene Copper Tape

Item	Test	Test method
Copper foil thickness (mm)	0.025±0.005	ASTM D374
Coating thickness (mm)	0.003±0.001	ASTM D374
Total thickness (mm)	0.04±0.005	ASTM D374
Proportion (g/cm ³)	7.70±0.50	ASTM D792
Temperature range (°C)	'-40-200	***
Thermal Conductivity (W/m-K)	400	ASTM D5470
Resistance (Ω.cm)	≤0.02	ASTM D257
Adhesion (kgf/inch)	>0.6	GB/T 2792-1998
Printability	Nano carbon coating	***
Width (mm)	380mm;500mm;600mm	Base of copper substrate
Length (M)	50M/ volume	***
RoHS	PASS	IEC 62321
Halogen	PASS	EN14582
REACH	PASS	EN14372

CR Technology, Inc

📍 55 Chase St. Methuen,
Massachusetts 01844

✉ sales@crtechinc.com

☎ 978.681.5300

Note: The information provided herein is accurate at time of publication. It is the responsibility of the end-user to confirm compliance to their application. All test data is typical. Therefore, these recommendations and data are for reference only and not as a product warranty.